

High Pressure Trailer Details: 530 MCF Capacity

Equipment Type	High-Pressure Gas Trailer
Manufacturer	CATEC
Model	CT-0753
Dimensions	Length: 53' / Wide: 8.5' / Hight: 10.1'
Weight	Tare Weight: 41,681 lb. / 18,902 kg. Full Loaded Weight: 65,282 lb. / 29,606 kg
Fueling	Can be configured for side-filled or rear filled
Connections	1' SAE port (up to 4 connections)
Axles	2 Axles
Cylinders	7 x 25" Type IV (Composites)
Age / Condition	New, Manufactured within last 3 years
Purchase Option	Purchase unit price set at \$750,000



Technical Data:

Manufacturer Stated Capacity	Gas Volume:	531,283 SCF 531 MCF 15,044 SCM / M3 4,194 GGE 3,692 DGE
	Water Volume:	12,397 Gal 46,928 Lit
Usable Capacity	510,000 SCF / 510 MCF (95% of the total volume)	
Pressure Range	Up to 4,000 psi (275 bars) to 300 psi (20 bars) to remain for liner integrity	
Re-Fill Time	At Compression Rate: @ 2000 scfm – 4 Hour 15 min @ 5000 scfm – 1 Hour 45 min	
Operating Temperature	Minimum: - 40 F/C / Maximum: 162F / 72C	
Cylinders	7 x 25" Type	

*If not included above, the serial number will be supplied to Lessee at time of delivery of the Rental Equipment.

Efficient:

High capacity and optimum pressure of 4,000 psi operating pressure equates to lower operating expenditure.

Modular:

Allows to easily scale supply in remote locations lacking pipeline infrastructure or in response to an emergency.

Safety:

Build in USA to ISO 11515 and approved under stringent US DOT and Transport Canada regulations.

Additional Info:

[Special Permit](#) (PDF)

[Emergency Response](#) (PDF)

[Operational Manual](#) (PDF)

Additional Pictures:



CNG Delivery		Doc. MANUAL CT-2793
Table 11 Cylinders and Trailer Operator's Manual		Rev. No. 3
Compu-Gas Advanced Technologies, LLC		Date 3-11-2018
		Page 2 of 26
		Approved by: G. Williams
Table of Contents		
Foreword	3	
Manual Purpose and How to Use	4	
Table of Contents	5	
Introduction	6	
Key Warnings	7	
Safety Precautions	8	
Who to Call for Assistance (for First Responders)	10	
General Specifications	11	
Pressure Range	11	
Safety Features	12	
Temperature Range	12	
Operating Procedure	13	
Filling Procedure	17	
Decant Sheet	20	
Gas Venting System - Pressure Relief Device & Balanced Actuator Valve	22	
Appendix A - Plumbing P&ID	24	

For more information on current availability and rental rates please contact our office at 1-800-909-4403 or send inquiry at info@cngdelivery.com